




SHARLIGHT ELECTRONICS CO., LTD.

SPECIFICATION FOR APPROVAL

Part No. : SLR-05021F-030

Package Dimensions

Viewing Angle



Notes: 1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25\text{mm}$ (.010") unless otherwise noted.
3. Protruded resin under flange is 1.0mm (.04") max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specifications are subject to change without notice.

Absolute Maximum Ratings at TA=25°C

Parameter	Maximum Rating	Unit
Power Dissipation	100	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	200	mA
Continuous Forward Current	30	mA
Derating Linear From 30°C	0.4	mA/°C
Reverse Voltage	5	V
Operating Temperature Range	-20°C to + 80°C	
Storage Temperature Range	-55°C to + 100°C	
Lead Soldering Temperature [1.6mm(.063") From Body]	260°C for 5 Seconds	

Electrical / Optical Characteristics at TA=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I_V		40		mcd	IF = 20mA
Viewing Angle	$2\theta_{1/2}$		45		deg	IF = 20mA
Peak Emission Wavelength	λ_p		565		nm	IF = 20mA
Dominant Wavelength	λ_d		569		nm	IF = 20mA
Spectral Line Half-Width	$\Delta\lambda$		30		nm	IF = 20mA
Forward Voltage	V_F		2.1	2.6	V	IF = 20mA
Reverse Current	IR			100	μA	VR = 5V


LISTER :

EDITOR :

DATE : 01-06-03

REV : 1

NO. : DS-32-02-0230



TYPICAL ELECTRON-OPTICAL CHARACTERISTIC CURVES 25°C Free Air Temperature Unless Otherwise Specified

