

LED 5 Spacer support

LED Series

Material: UL qualified nylon66(natural).

Usage: to protect LED over PC board and make the height consistent the middle support desigt to prevent the pins from bend.

break and short- circuit

Flame Class: 94V~2

Working Temperature:-20C ~ 120C

Part #	L
LED-2Y	2
LED-2.5Y	2.5
LED-2.5	
LED-3A	
LED-3Y	3
LED-3.5Y	3.5
LED-4Y	4
LED-4.5Y	4.5
LED-5Y	5
LED-5.5Y	5.5
LED-6Y	6
LED-6.5Y	6.5
LED-7Y	7
LED-7.5Y	7.5
LED-8.5Y	8
LED-8Y	8.5
LED-9Y	9
LED-9.5Y	9.5
LED-10Y	10
LED-10.5Y	10.5
LED-11Y	11
LED-11.5Y	11.5
LED-12Y	12
LED-12.5Y	12.5
LED-13Y	13
LED-13.5Y	13.5
LED-14Y	14
LED-14.5Y	14.5
LED-15Y	15
LED-15.5Y	15.5
LED-16Y	16
LED-16.5Y	16.5
LED-17Y	17
LED-17.5Y	17.5
LED-18Y	18
LED-18.5Y	18.5
LED-19Y	19
LED-19.5Y	19.5
LED-20Y	20
LED-20.5Y	20.5
LED-21.5Y	21
LED-21Y	21.5
LED-22Y	22
LED-22.5Y	22.5
LED-23Y	23
LED-23.5Y	23.5
LED-24Y	24
LED-24.5Y	24.5
LED-25Y	25
LED-25.5Y	25.5
LED-26Y	26

